

# 9100SP

## Mortice Sashlock with Anti-thrust latch for single-leaf fire-rated doors

### Premium Class




#### Features

Anti-thrust latch as mechanical latchbolt blocking mechanism
Prepared for euro-profile-cylinder
With transmission bar
Handed (left hand / right hand to be specified)
Centre distance 72 mm, backset 55 mm (60, 65, 70 and 80 mm)
Bushed TENAX clamp follower 8 mm, sintered steel
Forend 24 (20) x 235 mm, flush (rebated) doors, edged or rounded, satin stainless steel, stainless steel 1.4301 (AISI 304)
Lock case galvanized and blue lacquered
Triple latchbolt sintered steel, nickel-plated
(Solid) deadbolt steel, nickel-plated, double throw (20 mm)
Strike plate 0522, edged or rounded, satin stainless steel, non-handed
Screws included

#### Classification

EN 12209	3 X 8 1 0 G 2 B A 3 0
CE marked	Approved product, certificate no. 0432-CPR-00292-02
Certifire	Approved product, certificate no. CF 5418
Fire safety	Successful fire test to BS EN 1634-1 Timber door 30, 60, 90 and 120 minutes Steel door 30, 60, 90, 120 and 240 minutes


 **certifire** is a registered trademark of EXOVA WARRINGTON

#### Intumescent lock pack (not included in delivery)

required	For use on 60, 90, 120 minutes timber fire doors
not required	For use on 30 minutes timber fire doors and steel fire doors


CPR Declaration of Performance available for download on [www.ces.eu/en](http://www.ces.eu/en)

Subject to changes without notice. V11/18



Article number  
0522

Article number  
9100SP



Art.-Nr. 9100SP