

CES Security Solutions Ltd

Unit 6, Northpoint Ind Est

Enterprise Close

Rochester, Kent ME2 4LX

t +44 (0)1634 713 369

e info@cessecurity.co.uk

e info@ces.eu


www.cessecurity.co.uk



CES vario Flex

Over 140 type and
size variations
in one kit

Overview

Type		Modular kit
Part no:	CES vario Flex	 CVFPROFISSET
Classification		Profile cylinder with latch lever (PZW) DIN EN 12209: 2004-03 ³ M700F2BA ³⁰ , reversible latch
Distance		72 + 92 mm
Backset		30, 35, 40, 45 mm
Follower		10 mm, ⁹ or ⁸ mm with reducing sleeves
Latch bolt and dead bolt		Non-ferrous metal, nickel plated
Forend dimensions for rebated doors		Not available
Forend dimensions for flush doors		Flat forend: 16, 20, 24 mm U-forend: 24 x 6 mm
Forend square/rounded		Square
Forend of special length		Upon request
Handedness		Suitable for either side

CES vario Flex The system for narrow stile doors

Everything you need to carry with you to replace a defective lock of a narrow stile door is in our handy CES vario Flex System Professional Kit.

With CES vario Flex, all important reference values of the lock, such as centre distance, backset and even the distance between dead bolt and latch bolt can be variably adjusted.

This allows you to assemble a maximum of different lock variants using a minimum of parts so that you are excellently prepared for every situation you may be confronted with at the door.

As delivered, the lock case is set for a centre distance of ⁹² mm. If a distance of ⁷² mm is required, the lock case can be quickly and easily pushed together to the desired dimension.

The system comprises a lock case with the basic backset of ³⁰ mm. By simply pushing on the spacer strips included in the package, the backset can be increased to as much as ⁴⁵ mm. The assembly kit also includes dead bolt and latch bolt heads appropriate for the respective backset.

With different flat forends and a U-section forend, every possible lock variant can be reproduced. Moreover, two reducer sleeves permit a reduction of the follower from ¹⁰ to ⁹ and ⁸ mm, respectively.



K High quality

Tested according to DIN EN 12209:2004-03

K Short response times

No delay through ordering, waiting for the delivery and renewed travel to the site

K Quick fitting

Fitting is very simple and can always be performed following the easy-to-understand instructions.

K Reduced storage costs

With this innovative lock system, you can minimise the number of parts carried in stock and thus significantly reduce your tied-up capital.

K Simple reordering

To complete the kit again after a job, only those parts have to be reordered that have been consumed. For this purpose, CESlocks offers appropriate retrofit kits for each backset.



See it in action!

The CES vario Flex fitting video can be viewed at:
www.cessecurity.co.uk

* Professional Kit Part no.: CVFPROFISSET